

Giraffe Brand Thinner, 550

Production Specification

Product number	550
Product name	GIRAFFE Brand Thinner for 5500 Series Polyurethane Paint

Introduction

Recommended uses	For the dilution of TOY Brand 5500 Series Polyurethane paint (Two-component)
Product description	<ul style="list-style-type: none"> • Flammable liquid • Heavy metal (Pb,Hg,Cd,Cr) free, complies with GB18581-2001



Technical Data

Vehicle	Organic Solvents
Color	Transparent

Standard Packing

20 - litre tin set	550 : 20 litres in 20-litre tin
4- litre tin set	550 : 4 litres in 20-litre tin

Others Concern

Other Consideration 	<ul style="list-style-type: none"> • Stir well before use. • Close lid tightly after use and storage in a cool, dry and clean place at 0~35°C. • Coating condition should be strictly controlled under 0~35°C, RH ≤85%. • Application can be performed according to the working introduction by means of the recommended method and proper instrument. • Overcoat with conventional finishes only.
Health & Safety Precautions 	<ul style="list-style-type: none"> • Flashpoint 35°C. This product is inflammable. Keep away from sparks and open flames. No smoking should be permitted in the working area. • Provide adequate ventilation during paint application. • Use fume masks if spray application is used. Avoid skin contact and inhalation of spray mist. • If the product comes in contact with the skin, wash thoroughly with luke warm water and soap or suitable cleaner. • If the eyes are contaminated, flush with water for minimum 10 minutes or diluted boric acid solution and obtain medical attention at once. • Keep out of reach of children.