

Flower Odour-Less All-in-1 Sealer

Update: 19th October, 2013

PRODUCT SPECIFICATION

PRODUCT NUMBER	#985
PRODUCT NAME	Flower Odour-Less All-in-1 Sealer

INTRODUCTION

RECOMMENDED USES	interior masonry, plaster, concrete, brickwork, gypsum board etc.
PRODUCT DESCRIPTION	<p>This interior all-in-1 waterborne sealer is environmental-friendly, odourless, and with excellent binding and penetration power. Therefore, it is suitable for helping interior walls decorations.</p> <ul style="list-style-type: none"> • Good Opacity • Excellent binding power • Prevent absorption of topcoat by masonry substrate • Odourless • Comply with China Environmental Green Labeling HJ/T201-2005 • Comply with Safety Standard of Indoor Decorating and Refurbishing Material GB18582-2008

TECHNICAL DATA

VEHICLE	Acrylic copolymer			
COLOUR	White			
FINISH	Matt			
VOLUME SOLIDS	Approx. 34%			
TYPICAL DRY FILM THICKNESS	20 microns			
CALCULATED COVERAGE	* 15-17 sq. m/ L/ 1 coat (At 20 microns)			
DRYING TIME AT 25°C & 70% RH	Touch Dry	Hard Dry	Topcoating	
	1 hour	2 hours	Min. - 6 hours Max. - Indefinite	

* Based on theoretical consumption; factors such as paint colour, application methods, surrounding environment and substrate conditions will affect the actual consumption.

STANDARD PACKING

1L Tin	5L Tin	
--------	--------	--

Flower Odour-Less All-in-1 Sealer #985

SURFACE PREPARATION



MASONRY/CONCRETE SURFACES	<ul style="list-style-type: none"> • Surface must be stable, clean, dry, free from grease and contaminants before application. • New concrete should be stable and allowed to age for at least 4 weeks under normal drying conditions before application. • Surface water content and pH value must be less than 12% and 10 respectively.
----------------------------------	--

COMPLEMENTING PRODUCTS

TOPCOAT	
MASONRY/CONCRETE SURFACES	Flower Anti-Formaldehyde Odour-Less Interior Emulsion Paint FPAHK Series* Flower Odour-Less All-in-1 Wall Finish AA-HK Series* Flower Matt Latex Paint 000 Series Flower Premium Emulsion Paint 0100 Series* Flower Water-Borne Acrylic Wall Finish 0200 Series* Flower Gloss Latex Paint 0300 Series Flower Deluxe Wall Finish 0600HK Series* Flower Archsite Emulsion Paint 0900HK Series* Flower Super Hiding Wall Finish 3000 Series

* Sales in Hong Kong only

APPLICATION

APPLICATION METHOD	Brush, Roller or Airless Spray
REDUCTION RATIO BY VOLUME	Brush or Roller - Maximum 10% of water Airless Spray - Not necessary
REDUCTION/CLEANSING SOLVENT	Water
OTHER CONSIDERATIONS 	<ul style="list-style-type: none"> • For proper curing, the substrate surface temperature should be 8-35°C and the environment relative humidity should not exceed 85%. • Stir well before use. • Ensure the primer is completely dry before application. • Wash all equipments with water immediately after application. • Cover the lids tightly after use and store at a cool, dry place (4-35°C).
HEALTH & SAFETY PRECAUTIONS 	<ul style="list-style-type: none"> • Provide adequate ventilation during paint application. • Wear fume masks and protective clothing to avoid skin contact or inhalation of spray mist. • If the product comes in contact with the skin, wash thoroughly with luke warm water, and soap or suitable cleanser. • If the eyes are contaminated, flush with water or diluted boric acid solution for minimum 10 minutes and seek medical advice immediately. • Keep in place out of children's reach .

* Type of Regulation Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong : P10-11

VOC content (ready to use) ≤ 50 g/L

The information given in this sheet is for guidance only and no warranty is provided. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage arising out of such use.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development. It is the user's responsibility to check this sheet is current prior to using the product.

